

Analog Servo Drive

AZXBE25A8

Description


The AZXBE25A8 PWM servo drive is designed to drive brushless DC motors at a high switching frequency. To increase system reliability and to reduce cabling costs, the drive is designed for direct integration into your PCB. The AZXBE25A8 is fully protected against over-voltage, under-voltage, over-current, over-heating, invalid commutation, and short-circuits. A single digital output indicates operating status. The drive interfaces with digital controllers that have analog $\pm 10V$ output. The AZXBE25A8 can utilize either quadrature encoder inputs or Tachometer feedback for velocity control. This servo drive requires only a single unregulated isolated DC power supply, and is fully RoHS (Reduction of Hazardous Substances) compliant.

The AZXBE25A8 conforms to the following specifications and is designed to the Environmental Engineering Considerations as defined in MIL-STD-810F.

Extended Environment Performance		
Ambient Temperature	-40°C to +85°C (-40°F to +185°F)	
Storage Temperature	-50°C to +100°C (-58°F to +212°F)	
Thermal Shock	-40°C to +85°C (-40°F to +185°F) in 2 min.	
Relative Humidity	0 to 95% Non-Condensing	
Vibration	30 Grms for 5 min. in 3 axes	

See Part Numbering Information on last page of datasheet for additional ordering options. The AZX Series Hardware Installation Manual is available for download at www.a-m-c.com.

Power Range	
Peak Current	25 A
Continuous Current	12.5 A
Supply Voltage	10 - 80 VDC




	Features
 Four Quadrant Regenerative Operation Direct Board-to-Board Integration Lightweight High Switching Frequency Wide Temperature Range High Performance Thermal Dissipation 	 Encoder Velocity Mode Digital Fault Output Monitor 12VDC Operation Current Monitor Output Compact Size High Power Density
HARDWARE PROTECTION Over-Voltage Under-Voltage Over-Current Short-circuit (phase-phase) Short-circuit (phase-phase) Short-circuit (phase-ground) INPUTS/OUTPUTS Digital Fault Output Digital Inhibit Input Analog Current Monitor Analog Current Reference COMMUTATION Trapezoidal FEEDBACK SUPPORTED Incremental Encoder Hall Sensors Tachometer (± 60 VDC)	MODES OF OPERATION Current Duty Cycle (Open Loop) Encoder Velocity Tachometer Velocity MOTORS SUPPORTED Three Phase (Brushless) Single Phase (Brushed, Voice Coil, Inductive Load) COMMAND SOURCE ±10 V Analog AGENCY APPROVALS & COMPLIANCE CONSIDERATIONS CE Class A (LVD) CE Class A (EMC) RoHS MIL-STD-810F (as stated) MIL-STD-1275D (optional) MIL-STD-461E (optional) MIL-STD-704F (optional)

- UL/cUL Pending



BLOCK DIAGRAM



	Information on Approvals and Compliances		
CE	Compliant with European EMC Directive 2004/108/EC on Electromagnetic Compatibility (specifically EN 61000-6- 4:2007 for Emissions, Class A and EN 61000-6-2:2005 for Immunity, Performance Criteria A). LVD requirements of Directive 2006/95/EC (specifically, EN 60204-1:2004, a Low Voltage Directive to protect users from electrical shock).		
COMPLIANCE	RoHS (Reduction of Hazardous Substances) is intended to prevent hazardous substances such as lead from being manufactured in electrical and electronic equipment.		
MIL-STD-810F	Environmental Engineering Considerations and Laboratory Tests - (as stated)		
MIL-STD-1275D	Characteristics of 28 Volt DC Electrical Systems in Military Vehicles - (optional)		
MIL-STD-461E	Requirements for the Control of Electromagnetic Interference Characteristics of Subsystems and Equipment - (optional)		
MIL-STD-704F	Aircraft Electric Power Characteristics - (optional)		
MIL-HDBK-217	Reliability Prediction of Electronic Equipment (MTBF) - (optional)		





SPECIFICATIONS

Power Specifications			
Description	Units	Value	
DC Supply Voltage Range	VDC	10 - 80	
DC Bus Over Voltage Limit	VDC	88	
DC Bus Under Voltage Limit	VDC	9	
Maximum Peak Output Current ¹	A	25	
Maximum Continuous Output Current	A	12.5	
Maximum Continuous Output Power	W	950	
Maximum Power Dissipation at Continuous Current	W	50	
Minimum Load Inductance (Line-To-Line) ²	μH	100	
Internal Bus Capacitance ³	μF	30	
Low Voltage Supply Outputs	-	+6 VDC (30 mA)	
Switching Frequency	kHz	31	
	Control	Specifications	
Description	Units	Value	
Command Sources	-	±10 V Analog	
Feedback Supported	-	Halls, Incremental Encoder, Tachometer (± 60 VDC)	
Commutation Methods	-	Trapezoidal	
Modes of Operation	-	Current, Encoder Velocity, Duty Cycle, Tachometer Velocity	
Motors Supported	-	Three Phase (Brushless), Single Phase (Brushed, Voice Coil, Inductive Load)	
Hardware Protection	-	Invalid Commutation Feedback, Over Current, Over Temperature, Over Voltage, Under Voltage, Short Circuit (Phase-Phase & Phase-Ground)	
	Mechanica	al Specifications	
Description	Units	Value	
Agency Approvals	-	CE Class A (EMC), CE Class A (LVD), RoHS, MIL-STD-810F (as stated), MIL-STD- 1275D (optional), MIL-STD-461E (optional), MIL-STD-704F (optional), MIL-HDBK- 217 (optional), UL/cUL Pending	
Size (H x W x D)	mm (in)	76.2 x 50.8 x 22.9 (3 x 2 x 0.9)	
Weight	g (oz)	119.7 (4.2)	
Baseplate Operating Temperature Range ⁴	°C (°F)	-40 - 105 (-40 - 221)	
Ambient Temperature Range	°C (°F)	-40 - 85 (-40 - 185)	
Storage Temperature Range	°C (°F)	-50 - 100 (-58 - 212)	
	°C (°F)	-40 - 85 (-40 - 185) in 2 minutes	
Thermal Shock	U(F)		
Thermal Shock Vibration	Grms	30 for 5 minutes in 3 axes	
	· · · ·		
Vibration	· · · ·	30 for 5 minutes in 3 axes	
Vibration Relative Humidity	· · · ·	30 for 5 minutes in 3 axes 0 - 95% Non-Condensing	
Vibration Relative Humidity Form Factor	· · · ·	30 for 5 minutes in 3 axes 0 - 95% Non-Condensing PCB Mounted	

Notes

Maximum duration of peak current is ~2 seconds. Peak RMS value must not exceed continuous current rating of the drive. Lower inductance is acceptable for bus voltages well below maximum. Use external inductance to meet requirements. 1.

2.

It is required to connect a 100 μ F / 100 V external bus capacitor between High Voltage and Power Ground. Additional cooling and/or heatsink may be required to achieve rated performance. 3.

4.





PIN FUNCTIONS

P1 - Signal Connector			
Pin	Name	Description / Notes	I/O
1	+REF IN	Differential Reference Input (±10 V Operating Range, ±15 V Maximum Input)	I
2	SIGNAL GND	Signal Ground	GND
3	-REF IN	Differential Reference Input (±10 V Operating Range, ±15 V Maximum Input)	I
4	CURRENT MONITOR	Current Monitor. Analog output signal proportional to the actual current output. Scaling is 13.3 A/V. Measure relative to signal ground.	0
5		TTL level (+5 V) inhibit/enable input. Leave open to enable drive. Pull to ground to inhibit drive. Inhibit turns off all power devices.	I
6	+V HALL OUT	Low Power Supply For Hall Sensors (+6 V @ 30 mA). Referenced to signal ground. Short circuit protected.	0
7	SIGNAL GND	Signal Ground	GND
8	HALL 1		I
9	HALL 2*	Single-ended Hall/Commutation Sensor Inputs (+5 V logic level).	I
10	HALL 3		
11	CURRENT REFERENCE	Measures the command signal to the internal current-loop. This pin has a maximum output of ±7.23 V when the drive outputs maximum peak current. Measure relative to signal ground.	0
12	FAULT OUT	TTL level (+5 V) output becomes high when power devices are disabled due to at least one of the following conditions: inhibit, invalid Hall state, output short circuit, over voltage, over temperature, power-up reset.	0
13	ENCODER-B IN	Single-ended encoder channel B input. +5 V logic level.	I
14	ENCODER-A IN	Single-ended encoder channel A input. +5 V logic level.	I
15	VEL MONITOR OUT / TACH IN	Velocity Monitor. Analog output proportional to motor speed. In Encoder Velocity mode, output is proportional to the encoder line frequency. Encoder Velocity scaling is 22 kHz/V. For Tachometer Velocity mode, feedback voltage range is ± 60 VDC max.	O\I
16	OFFSET	Connection to external resistance for command offset adjustments. Apply a \pm VDC (10V Max) signal through an external potentiometer into this pin to offset the input gain.	Ι

P2 and P3 - Power Connector

Р	in	Name	Description / Notes	I/O
1b	1a	HIGH VOLTAGE	DC Power Input. 3A Continuous Current Rating Per Pin. It is required to connect a 100 μ F /	I
2b	2a	HIGH VOLTAGE	100 V external capacitor between High Voltage and Power Ground.	I
3b		NC	Not Connected (Reserved)	-
	3a	NC (KEY)	Key: No Connection (pin removed) for P2. Not Connected (Reserved) for P3.	-
4b	4a	PWR GND	Power Ground (Common With Signal Ground). 3A Continuous Current Rating Per Pin	
5b	5a	PWR GND		
6b	6a	MOTOR C		
7b	7a MOTOR C			0
8b	8a	MOTOR B*	Motor Phase Outputs. Current output distributed equally across 4 pins per motor phase, 3A	0
9b	9a	MOTOR B*	continuous current carrying capacity per pin.	0
10b	10a	MOTOR A*		0
11b	11a	MOTOR A*		0
* -			nd Hall O and anky connect motion loads to Materia A and Materia	

*For use with Single Phase (Brushed) motors, ground Hall 2 and only connect motor leads to Motor A and Motor B.





HARDWARE SETTINGS

Switch Functions

Switch	Description	Setting	
Switch	Description	On	Off
1	Duty Cycle mode selector. Activates internal PWM feedback.	Duty Cycle mode	Other modes
2	Activate velocity feedback or monitor. For Encoder Velocity mode, activates feedback. For Current mode, activates velocity monitor.	Active	Inactive
3	Current mode selector.	Current mode	Other modes
4	Velocity feedback polarity. Changes the polarity of the internal feedback signal and the velocity monitor output signal. Inversion of the feedback polarity may be required to prevent a motor runaway condition.	Standard	Inverted

Mode Selection Table

	SW1	SW2	SW3
CURRENT	OFF	ON	ON
DUTY CYCLE	ON	OFF	OFF
ENCODER VELOCITY*	OFF	ON	OFF
TACHOMETER VELOCITY	OFF	OFF	OFF

*NOTE: See details of switch 4 for further Encoder Velocity configuration information.

Jumper Settings

The drive PCB is conformal coated, thereby making it difficult to change jumper settings. Jumpers are SMT 0 ohm resistors located on the underside of the drive PCB. By default, the drive is configured with the jumpers installed. Typical drive operation will not require the jumpers to be removed. Please contact the factory before jumper removal.

Jumper	Description	Config	uration
	SMT Jumper (0Ω Resistor)	Not Installed	Installed
JE1	Inhibit logic. Sets the logic level of inhibit pins. Labeled JE1 on the PCB of the drive.	Low Enable	Low Inhibit
JE2	Hall sensor phasing. Selects 120 or 60 degree commutation phasing. Labeled JE2 on the PCB of the drive.	60 degree	120 degree

Potentiometer Functions

Potentiometers are located between the PCB and the drive baseplate, and are accesible from the side. Potentiometers are approximately linear and have 12 active turns with 1 inactive turn on each end.

Potentiometer	Description	Turning CW
1	Loop gain adjustment for duty cycle / velocity modes. Turn this pot fully CCW in current mode. Located closest to the corner of the PCB.	Increases gain
2	Offset. Used to adjust any imbalance in the input signal or in the amplifier. Located furthest from the corner of the PCB.	Adjusts offset in negative direction






MECHANICAL INFORMATION

	P1 - Signal Connector		
Connector Information		16-pin, 2.54 mm spaced header	
Mating Connector	Details	Samtec: BCS-116-L-S-PE	
Mating Connector	Included with Drive	No	
		15 VELMONITOR OUT / TACH IN 13 ENCODERB IN 9 HALL 2 1 CURRENT REFERENCE 9 HALL 2 1 SIGNAL GND 2 SIGNAL GND 4 CURRENT MONITOR 4 CURRENT MONITOR 10 HALL 3 10	


P2 - Power Connector		
Connector Information		22-pin, 2.54 mm spaced, dual-row header
Mating Connector	Details	Samtec: SSM-111-L-DV
	Included with Drive	No
PWR GND 5a PWR GND 5a HIGH VOLTAGE 1a HIGH VOLTAGE 1b PWR GND 4a HIGH VOLTAGE 1b PWR GND 5b PWR GND 5b PWR GND 5b PWR GND 5b PWR GND 5b PWR GND 5b PWR GND 5b Fight Control C Fight		







MOUNTING DIMENSIONS








www.electromate.com

PART NUMBERING INFORMATION



ADVANCED Motion Controls' AZ series of servo drives are available in many configurations. Note that not all possible part number combinations are offered as standard drives. All models listed in the selection tables of the website are readily available, standard product offerings.

ADVANCED Motion Controls also has the capability to promptly develop and deliver specified products for OEMs with volume requests. Our Applications and Engineering Departments will work closely with your design team through all stages of development in order to provide the best servo drive solution for your system. Equipped with on-site manufacturing for quickturn customs capabilities, ADVANCED Motion Controls utilizes our years of engineering and manufacturing expertise to decrease your costs and time-to-market while increasing system quality and reliability.

Examples of Modifications and Customized Products


- Integration of Drive into Motor Housing
- Mount OEM PCB onto Drive Without Cables
- Multi-axis Configuration for Compact System
- Custom PCB and Baseplate for Optimized Footprint
- **RTV/Epoxy** Components for High Vibration
- OEM Specified Connectors for Instant Compatibility
- OEM Specified Silkscreen for Custom Appearance
- Increased Thermal Limits for High Temp. Operation
- Integrate OEM Circuitry onto Drive PCB
 - 4
 - Custom Control Loop Tuned to Motor Characteristics
 - Custom I/O Interface for System Compatibility Preset Switches and Pots to Reduce User Setup
 - **Optimized Switching Frequency**

 - Ramped Velocity Command for Smooth Acceleration
 - Remove Unused Features to Reduce OEM Cost
 - Application Specific Current and Voltage Limits

Feel free to contact Applications Engineering for further information and details.

Available Accessories

ADVANCED Motion Controls offers a variety of accessories designed to facilitate drive integration into a servo system. Visit www.a-m-c.com to see which accessories will assist with your application design and implementation.



ctromate.com All specifications in this document are subject to change without written notice. Actual product may differ from pictures provided in this document.