Galil Motion Control



RIO-574x0

Data Sheet

Sold & Serviced By: CONCENTION ELECTROMATE Toll Free Phone (877) SERV098 Toll Free Fax (877) SERV099 www.electromate.com sales@electromate.com

Product Description

The RIO-574x0 is a compact, cost-effective EtherCAT I/O slave module. It is packed with digital and analog I/O to be used remotely in an EtherCAT automation system. Although the RIO-57000 can be used with a generic EtherCAT master, it is designed to integrate seamlessly into an EtherCAT system with Galil's DMC-500x0 EtherCAT master.

Each RIO-574x0 has 16 optoisolated digital inputs and 16 high-power, 500mA sourcing, optoisolated digital outputs. The RIO-57420 is expanded to include 8 analog inputs and 8 analog outputs, both configurable in the ranges of 0-5V, 0-10V, ±5V, or ±10V.

The RIO-574x0 can be configured over USB in a few steps using Galil's software and intuitive english-like 2 letter commands.



Features

- EtherCAT I/O slave module that is compact and cost-effective
- 2 EtherCAT ports and 1 USB port (for configuration)
- Analog & Digital I/O
 - 16 optically isolated inputs
 - 16 optically isolated 500mA outputs
 - 8 analog inputs (on select models) 12bit*
 - 8 analog outputs (on select models) 12bit*
- Easy integration with Galil's DMC-500x0 EtherCAT master
- LED indicators for all digital I/O points
- Easy-to-use, 2-letter Galil programming language
- 4.24" x 4.81" x 2.35"; Metal enclosure with DIN clips
- Screw terminal connectors
- Custom hardware and firmware options available

*16bit option available

Sold & Serviced By: CONTROMATE Toll Free Phone (877) SERV098 Toll Free Fax (877) SERV099 www.electromate.com sales@electromate.com

Specifications

Power and Mechanical			
Power requirements	9-48 V _{DC}		
Operational temperature	0 – 70 deg C		
Humidity	20 – 95 % RH, non-condensing		
Dimensions	4.24 × 4.81 × 2.35 inches		



General Purpose I/O					
	Number of I/O		Voltago	Details	
	RIO-57410	RIO-57420	Voltage	Details	
Optoisolated	16	16 5-24 V _{DC}	Can be wired as either		
inputs	10	10	J 24 V _{DC}	active high or active low.	
Optoisolated	16	16	12-24 V _{DC}	500mA Sourcing	
outputs	10	10			
Analog Inputs	None	8	±10, ±5, 0-5, 0-10 V	12 bit, 16 bit optional, 4-	
			±10, ±5, 0-5, 0-10 v	20mA optional	
Analog Outputs None 8	0		4mA sink/source, 12 bit,		
	NOTIE 8	0	±10, ±5, 0-5, 0-10 V	16 bit optional	



Ordering Options

Use the Part Number Generator for building your RIO-57000 http://www.galil.com/order/part-number-generator/rio-574x0#RIO-57410

RIO-574x0					
Options					
Part Number	Description				
RIO-57410	EtherCAT PLC with 32 Digital I/O				
RIO-57420	EtherCAT PLC with 32 Digital I/O and 16 Analog I/O				
(NO DIN)	DIN Rail Mount not included (unit comes default with DIN)				
(16bit)	16-bit analog inputs				
(4-20mA)	4-20mA analog inputs				



Accessories		
	Part Number	Description
	PS-2.50-24	60 Watt Power Supply (2.5 Amps @ 24V)
	GalilSuite	Servo Tuning and Analysis with Program Editor and Terminal
	GalilTools	GalilTools programming software for Galil controllers

