



IXARC Absolute Rotary Encoder

OCD-EIB1B-0016-S060-PRM



Interface

| | |
|-----------------------|---|
| Interface | Profinet |
| Profile | Profidrive Profile 4.x, Encoder Profile 4.x |
| Diagnostics | Memory |
| Features | Boot-Loader, Round Axis, Flashing LEDs |
| Transmission Rate | 10 / 100 Mbit |
| Interface Cycle Time | ≥ 1 ms |
| Programming Functions | Resolution, time base and filter for velocity, preset, counting direction, IP-Address |

Outputs

| | |
|---------------|----------|
| Output Driver | Ethernet |
|---------------|----------|

Electrical Data

| | |
|-----------------------------|--|
| Supply Voltage | 10 - 30 VDC |
| Current Consumption | ≤ 230 mA @ 10 V DC, ≤ 100 mA @ 24 V DC |
| Power Consumption | ≤ 2.5 W |
| Start-Up Time | < 1 s |
| Reverse Polarity Protection | Yes |
| Short Circuit Protection | Yes |
| EMC: Emitted Interference | DIN EN 61000-6-4 |
| EMC: Noise Immunity | DIN EN 61000-6-2 |

POSITAL

FRABA



MTTF 65 years @ 40 °C

Sensor

| | |
|-----------------------|--|
| Technology | Optical |
| Resolution Singleturn | 16 bit |
| Accuracy (INL) | ±0.0220° (14 - 16 bit), ±0.0439° (≤13 bit) |
| Code | Binary |

Environmental Specifications

| | |
|----------------------------|------------------------------------|
| Protection Class (Shaft) | IP65 |
| Protection Class (Housing) | IP65 |
| Operating Temperature | -40 °C (-40 °F) - +85 °C (+185 °F) |
| Storage Temperature | -40 °C (-40 °F) - +85 °C (+185 °F) |
| Humidity | 98% RH, no condensation |

Mechanical Data

| | |
|--|---|
| Housing Material | Steel |
| Housing Coating | Wet coating (RAL 9006 White Aluminium) + Cathodic corrosion protection (>720 h salt spray resistance) |
| Flange Type | Synchro, ø 58 mm (S) |
| Flange Material | Aluminum |
| Shaft Type | Solid, Length = 10 mm |
| Shaft Diameter | ø 6 mm (0.24") |
| Shaft Material | Stainless Steel V2A (1.4305, 303) |
| Max. Shaft Load | Axial 40 N, Radial 110 N |
| Minimum Mechanical Lifetime (10 ⁸ revolutions with Fa/Fr) | 550 (20 N / 40 N), 195 (40 N / 60 N), 135 (40 N / 80 N), 85 (40 N / 110 N) |
| Rotor Inertia | ≤ 30 gcm ² [≤ 0.17 oz-in ²] |
| Friction Torque | ≤ 3 Ncm @ 20 °C (4.2 oz-in @ 68 °F) |
| Max. Permissible Mechanical Speed | ≤ 12000 1/min |
| Shock Resistance | ≤ 100 g (half sine 6 ms, EN 60068-2-27) |
| Permanent Shock Resistance | ≤ 10 g (half sine 16 ms, EN 60068-2-29) |
| Vibration Resistance | ≤ 10 g (10 Hz - 1000 Hz, EN 60068-2-6) |
| Length | 73 mm (2.87") |
| Weight | 345 g (0.76 lb) |

Electrical Connection

Data Sheet

Printed at 8-10-2020 14:10

POSITAL

FRABA



| | |
|------------------------|-----------------------------|
| Connection Orientation | Radial |
| Connector 1 | M12, Female, 4 pin, d coded |
| Connector 2 | M12, Male, 4 pin, a coded |
| Connector 3 | M12, Female, 4 pin, d coded |

Product Life Cycle

| | |
|--------------------|-------------|
| Product Life Cycle | Established |
| Approval | CE |



Connection Plan

| SIGNAL | CONNECTOR | PIN NUMBER |
|---------------|-------------|------------|
| Tx+ | Connector 1 | 1 |
| Rx+ | Connector 1 | 2 |
| Tx- | Connector 1 | 3 |
| Rx- | Connector 1 | 4 |
| Power Supply | Connector 2 | 1 |
| Not Connected | Connector 2 | 2 |
| GND | Connector 2 | 3 |
| Not Connected | Connector 2 | 4 |
| Tx+ | Connector 3 | 1 |
| Rx+ | Connector 3 | 2 |
| Tx- | Connector 3 | 3 |
| Rx- | Connector 3 | 4 |

Connector-View on Encoder

Dimensional Drawing

[2D Drawing](#)

Accessories

Connectors & Cables

Data Sheet
Printed at 8-10-2020 14:10

POSITAL

FRABA



2m PUR Cable, 4pin, D-Coded, m
M12, 4pin A-Coded, Female
10m PUR Cable, 4pin, D-Coded, m
10m PVC Cable, 4pin, D-Coded, m
2m PVC Cable, 4pin, D-Coded, m
5m PVC Cable, 4pin, D-Coded, m
POS M12 5pin-A Female+5m PUR Cable
POS M12 5pin-A Female+2m PUR Cable
POS M12 5pin-A Female+10m PUR Cable
M12, 4pin D-Coded, Male
M12, 5pin A-Coded, Female
5m PUR Cable, 4pin, D-Coded, m

More

Couplings

Coupling Bellow Type-06-06
Coupling Bellow Type-06-10
Coupling Bellow Type-06-08
Coupling Bellow Type-06-(3/8")
Coupling Bellow Type-06-(1/4")
Coupling Jaw Type-06-06
Coupling Jaw Type-06-10
Coupling Jaw Type-06-08
Coupling Jaw Type-06-12
Coupling Jaw Type-06-(1/4")
Coupling Jaw Type-06-(3/8")
Coupling Disc Type-06-06
Coupling Disc Type-06-10

More

Adapter Flanges

Mounting Bracket for Synchro Flange w/ fixtures

Clamping Rings

Clamp Disc w/ Eccentric Hole-4pcs

Clamp Disc w/ Centred Hole-4pcs

Got questions? Need an individual solution? We are here to help!

Data Sheet

Printed at 8-10-2020 14:10

POSITAL

FRABA



Sold & Serviced By:



Canadian and International Sales

ELECTROMATE

877-737-8698

sales@electromate.com

www.electromate.com

U.S. Sales

SERVO2GO.com

877-378-0240

sales@servo2go.com

www.servo2go.com

The picture and drawing are for general presentation purposes only. Please refer to the "Download" section for detailed technical drawings. All dimension in [inch] mm. © FRABA B.V., All rights reserved. We do not assume responsibility for technical inaccuracies or omissions. Specifications are subject to change without notice.

Data Sheet

Printed at 8-10-2020 14:10